

## SAFETY DATA SHEET

### Metal PROTECT Concentrate

### **Section 1. Identification**

Product identifier : Metal PROTECT Concentrate

Product code : Not available.

Other means of : Not available.

identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Preparation on the basis of hybrid materials in an ethanol solution for the dirt repellent

coating of glass surfaces.

Supplier's details : SiO2 Innovation Labs inc.

345 Wilson Ave., suite 306

Toronto, ON Canada M3H 5W1

Tel: 1-416-469-5000 Email: info@sio2.ca Web: sio2.ca

Emergency telephone number (with hours of

operation)

: 1-416-469-5000

24/7

### Section 2. Hazard identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1

#### **GHS label elements**

Hazard pictograms







Signal word : Danger

**Hazard statements** : H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation. H370 - Causes damage to organs.

**Precautionary statements** 

Prevention : P280 - Wear protective gloves. Wear protective clothing. Wear eye or face

protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.



### Section 2. Hazard identification

Response : P308 + P311 - IF exposed or concerned: Call a POISON CENTER or physician.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of : Not available.
identification

Ingredient name	% (w/w)	CAS number
Ethanol	80 - 100	64-17-5
Methanol	1 - 5	67-56-1

The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

### **Description of necessary first aid measures**

Eye contact : Immediate

Inhalation

Skin contact

Ingestion

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention. If necessary, call a poison center or physician.

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

: Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. If necessary, call a poison center or physician.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed





### Section 4. First-aid measures

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Do not use water jet or water-based fire extinguishers.

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.





### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

### Spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials



### Section 7. Handling and storage

before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
Ethanol	CA Alberta Provincial (Canada, 4/2009).  8 hrs OEL: 1000 ppm 8 hours.  8 hrs OEL: 1880 mg/m³ 8 hours.  CA British Columbia Provincial (Canada, 6/2017).  STEL: 1000 ppm 15 minutes.  CA Ontario Provincial (Canada, 1/2018).  STEL: 1000 ppm 15 minutes.  CA Quebec Provincial (Canada, 1/2014).  TWAEV: 1000 ppm 8 hours.  TWAEV: 1880 mg/m³ 8 hours.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 1250 ppm 15 minutes.
Methanol	TWA: 1000 ppm 8 hours.  CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 262 mg/m³ 8 hours. 8 hrs OEL: 200 ppm 8 hours. 15 min OEL: 250 ppm 15 minutes. 15 min OEL: 328 mg/m³ 15 minutes. CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 250 ppm 15 minutes. CA Ontario Provincial (Canada, 1/2018). Absorbed through skin. TWA: 200 ppm 8 hours. STEL: 250 ppm 15 minutes.
	CA Quebec Provincial (Canada, 1/2014). Absorbed through skin.  TWAEV: 200 ppm 8 hours.  TWAEV: 262 mg/m³ 8 hours.  STEV: 250 ppm 15 minutes.  STEV: 328 mg/m³ 15 minutes.  CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin.  STEL: 250 ppm 15 minutes.  TWA: 200 ppm 8 hours.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.





### Section 8. Exposure controls/personal protection

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Liquid.

Color : Not available.

Odor : Not available.

Odor threshold : Not available.

**pH** : 6-7

Melting point : Not available.

Boiling point : 78 ° C (172.4F)

Flash point : Closed cup: >17°C (62.6°F) [Pensky-Martens.]

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : 0.825

Partition coefficient: noctanol/water

Auto-ignition temperature

Decomposition temperature

: Not available.

Not available.

Not available.





### Section 9. Physical and chemical properties

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials**: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m³ 7 g/kg	4 hours
Methanol	LC50 Inhalation Gas. LC50 Inhalation Gas. LD50 Dermal LD50 Oral	Rat Rat Rabbit Rat	145000 ppm 64000 ppm 15800 mg/kg 5600 mg/kg	1 hours 4 hours -

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 µl	-
	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	500 mg 400 mg	-

### **Sensitization**

There is no data available.

#### **Mutagenicity**

There is no data available.

### **Carcinogenicity**

There is no data available.

### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

Specific target organ toxicity (single exposure)





### **Section 11. Toxicological information**

Name	Category	Target organs
Methanol	Category 1	Not determined

### Specific target organ toxicity (repeated exposure)

There is no data available.

#### **Aspiration hazard**

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

### Delayed and immediate effects and also chronic effects from short and long term exposure

### **Short term exposure**

**Potential immediate** : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

**Potential immediate** : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

### Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

### **Numerical measures of toxicity**

**Acute toxicity estimates** 





### **Section 11. Toxicological information**

Route	ATE value
Oral	2121.3 mg/kg
Dermal	6364 mg/kg
Inhalation (vapors)	63.64 mg/L

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Ethanol	Acute EC50 1074 mg/L Fresh water Acute LC50 5680 mg/L Fresh water Acute LC50 11000000 µg/L Marine water Chronic NOEC 4.995 mg/L Marine water Chronic NOEC 100 ul/L Fresh water Chronic NOEC 0.375 ul/L Fresh water Acute LC50 2500000 µg/L Marine water Acute LC50 3289 mg/L Fresh water Acute LC50 290 mg/L Fresh water	Crustaceans - Cypris subglobosa Daphnia - Daphnia magna - Neonate Fish - Alburnus alburnus Algae - Ulva pertusa Daphnia - Daphnia magna - Neonate Fish - Gambusia holbrooki - Larvae Crustaceans - Crangon crangon - Adult Daphnia - Daphnia magna - Neonate Fish - Danio rerio - Egg	48 hours 48 hours 96 hours 96 hours 21 days 12 weeks 48 hours 48 hours 96 hours

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Ethanol	-0.35	-	low
Methanol	-0.77	<10	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





### **Section 14. Transport information**

	TDG Classification	IMDG	IATA
UN number	UN1993	UN1993	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol)	FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol)	FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol)
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	No.	No.	No.

**Additional information** 

**TDG Classification**: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.18-2.19 (Class 3).

**IMDG** : **Emergency schedules** F-E, S-E

Emergency Response Guidebook (ERG)

: 128

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do

in the event of an accident or spillage.

: All components are listed or exempted.

### Section 15. Regulatory information

**Canadian lists** 

Canada inventory (DSL

NDSL)

Canadian NPRI : The following components are listed: Ethanol; Methanol

**CEPA Toxic substances**: None of the components are listed.

### **Section 16. Other information**

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	On basis of test data Calculation method Calculation method

**History** 

Date of issue : 02/15/2017

Date of previous issue : Not applicable

Version : 1

Prepared by : KMK Regulatory Services Inc.





### Section 16. Other information

**Key to abbreviations** 

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

HPR = Hazardous Products Regulations

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

